



PennWest

**Harmon Valley South HCSS Pilot Approval 11895
Annual Performance Presentation**

11-Feb-2015

1. Background
2. Geology
3. Drilling and Completions
4. Artificial Lift
5. Well Instrumentation
6. 4D Seismic
7. Scheme Performance
8. Future Plans

- 1. Background**
2. Geology
3. Drilling and Completions
4. Artificial Lift
5. Well Instrumentation
6. 4D Seismic
7. Scheme Performance
8. Future Plans

- Primary scheme development began in 2004 under Approval No. 11060
- The Harmon Valley South (HVS) Primary field has 18 primary wells operating on 8 wellpads
- Currently there are 30 wells within 1,000m of the HVS Pilot Project, both primary producing and stratigraphic wells

Background – Thermal Approval

PennWest

| | | |
|------------------------------------|-----------|---|
| Approval 11895 | 21-Sep-12 | Original Pilot Approval |
| Approval 11895A | 28-Nov-12 | Revised bottomhole location for pilot wells |
| AUC Approval for Pilot Power Plant | 3-Oct-12 | AUC Approval received |
| Approval 11895B | 3-Mar-14 | Increase maximum bottomhole operating pressure from 14,500 kPag to 21,500 kPag and light hydrocarbon circulation prior to steam injection |
| Approval 11895C | 11-Aug-14 | Increase steam injection volume above 14,500 kPag from 2,500 m ³ to 12,500 m ³ and reduction in maximum bottomhole injection pressure from 21,500 kPag to 20,000 kPag |

- A three well HCSS project in the Bluesky Formation
- 80% quality steam injected at the heel of the well
- Inject steam at a target rate of 500 m³/d CWE
- Evaluate technology in various reservoir conditions:
 - Well 100/07-36: Tight, viscous conditions
 - Well 102/15-06: High water saturation
 - Well 103/14-06: High permeability


1. Background
- 2. Geology**
3. Drilling and Completions
4. Artificial Lift
5. Well Instrumentation
6. 4D Seismic
7. Scheme Performance
8. Future Plans

Geology – Bluesky Formation Overview

PennWest

- Series of north/south oriented, stacked tidal distributary channels
- Fine to medium grained litharenite
- Average depth is 675m TVD
- Thickness up to 26m
- Porosities from 24% to 30% (Avg 25%)
- Permeability from 450 to 4,200 mD
- Oil Saturation from 55% to 85% (Avg 76%)
- API Gravities of 8.7 to 9.8 API at 15.6°C
- Viscosities from 11,000 to 300,000 cSt at 20°C

10-06-083-17W5 Type Log



Geology – Thermal Pilot Location


PennWest

■ Pilot HCSS Wells


- 100/07-36-082-18W5
- 102/15-06-083-17W5
- 103/14-06-083-17W5

■ Observation Wells

- 100/10-06-083-17W5
- 100/15-06-083-17W5
- 102/14-06-083-17W5
- 100/15-36-082-18W5
- 100/02-06-083-17W5
- 100/11-06-083-17W5





- 3D-HVS09 (North)
 - Shot in January 2009
 - Processed in January 2009
- 3D-HVS (South)
 - Shot in March 2008
 - Processed in March 2008



Geology – Bluesky Top Structure Map

PennWest


| | | |
|---|-----------------|--------------------------------------|
| PennWest Exploration | | |
| Bluesky Structure (mss) | | |
| Licensed to : Penn West Petroleum | | |
|  | By : JW | Date : 2012/11/30 |
| | Scale = 1:12000 | Project : Seal Regional Oct 28, 2011 |



Geology – Bluesky Base Structure Map

PennWest


| | | |
|-----------------------------------|-----------------|-------------------------------------|
| PennWest Exploration | | |
| Bluesky Base Structure (mss) | | |
| Licensed to : Penn West Petroleum | | |
| geoSCOUT www.geoscout.com | By : JW | Date : 2012/11/30 |
| | Scale = 1:12000 | Project : Seal Regional Oct 28 2011 |



Geology – Net Pay Map

PennWest


| | | |
|---|-----------------|--------------------------------------|
| PennWest Exploration | | |
| Bluesky Net Pay (m) (Phi>24%, Res>20 ohmm) | | |
| Licensed to : PennWest Petroleum | By : JW | Date : 2012/11/30 |
| geoSCOUT www.geoscout.com | Scale = 1:12000 | Project : Seal Regional Oct 28, 2011 |



Geology – Structural Cross-Section

PennWest


| | | |
|--|----------------------------|--|
| PennWest Exploration | | |
| Harmon Valley South Thermal Pilot HCSS Structural Cross-section | | |
| Licensed to : Penn West Petroleum | | |
| geoSCOUT www.geoscout.com | By : JW Scale = 1:12000 | Date : 2012/11/30 Project : Seal Regional Oct 28 2011 |



Geology – Structural Cross-Section

100/07-36-082-18W5


PennWest



Geology – Structural Cross-Section


102/15-06-083-17W5

PennWest



Geology – Structural Cross-Section 103/14-06-083-17W5

PennWest



Geology - Cored Wells


PennWest



Cored Wells



CSS Thermal Well



Geology – Core Photos

PennWest

PENN WEST ENERGY INC.
PENN WEST WALRUS 00/10-06-083-17 W5M/0

52139-11-5270 F02
52140-11-1146
March 14, 2011

Core #1

Top 684.09 m



Bottom 688.59 m




PENN WEST ENERGY INC.
PENN WEST WALRUS 00/15-06-083-17 W5M/0

52139-11-5305 F03
52140-11-1177
March 20, 2011

Core #2

Top 685.96 m



Bottom 689.59 m



Geology – Average Reservoir Properties (Pilot) **PennWest**

| | |
|--|--------|
| Net pay (m) | 14.7 |
| Area (ha) | 184 |
| Porosity (%) | 27 |
| Water Saturation (%) | 24 |
| Formation Temperature (°C) | 22 |
| Formation Pressure (kPa) | 4,800 |
| Viscosity (cSt at 20°C) | 30,000 |
| Average Hz Permeability (mD) | 1,500 |
| Formation Volume Factor | 1.02 |
| OBIP (e ³ m ³)* | 5,441 |

*Based on the pilot project area


- In 2011, a mini-frac test was conducted in 100/03-06-083-17W5
- Penn West performed two new MDT mini-frac tests to determine the closure stress in the Wilrich and Bluesky Formations:
 - Wilrich Fm depth of 672m MD
 - Bluesky Fm depth of 698m MD
- After processing the data, the following gradients are calculated:

| | Mini-frac Results | | | |
|----------|-------------------|------------|----------|------------|
| Zone | Depth (m) | Min Stress | Gradient | Direction |
| | (MD) | (kPa) | (kPa/m) | |
| Wilwrich | 672 | 16,000 | 23.8 | horizontal |
| Bluesky | 698 | 12,600 | 18.1 | vertical |

- The MOP granted by the AER for the pilot is 20MPa (29.8 kPa / m)

1. Background
2. Geology
- 3. Drilling and Completions**
4. Artificial Lift
5. Well Instrumentation
6. 4D Seismic
7. Scheme Performance
8. Future Plans

- 60.3mm guide string to the toe
- 38.1mm coil tubing thermocouple instrumentation line inside the guide string
- 114.3mm injection and production string landed at the heel
- Bubble tube strapped to the guide string



1. Background
2. Geology
3. Drilling and Completions
- 4. Artificial Lift**
5. Well Instrumentation
6. 4D Seismic
7. Scheme Performance
8. Future Plans

- 3.25" insert rod pumps run on all three wells initially
- Due to low reservoir temperatures in Well 103/14-06 following steam cycle 1, pump could not produce the viscous oil
 - Weatherford 56-1500 Insert PCP run in May 2014 to enable continued production
 - Intend to return to rod pump following second steam cycle on Well 103/14-06

1. Background
2. Geology
3. Drilling and Completions
4. Artificial Lift
- 5. Well Instrumentation**
6. 4D Seismic
7. Scheme Performance
8. Future Plans

- Multiple thermocouples to monitor temperature from wellhead to the toe of the well (1,600 – 1,800m MD)
- Heel pressure measurement via bubble tube strapped to the 60.3mm guide string
- Toe pressure measurement via bubble tube in instrumentation coil
- Ability to perform N₂ purge from surface

- Five observation wells to measure reservoir response at various locations along the horizontal lengths of the wells
- Real-time pressure and temperature monitoring via thermocouples and single point pressure gauges spaced in the reservoir
- Permanent passive micro-seismic monitoring from 2 observation wells to monitor casing and caprock integrity


1. Background
2. Geology
3. Drilling and Completions
4. Artificial Lift
5. Well Instrumentation
- 6. 4D Seismic**
7. Scheme Performance
8. Future Plans

- No current plans to conduct 4D Seismic at HVS

1. Background
2. Geology
3. Drilling and Completions
4. Artificial Lift
5. Well Instrumentation
6. 4D Seismic
- 7. Scheme Performance**
8. Future Plans


Scheme Performance – Well 100/07-36

PennWest




Scheme Performance – Well 100/07-36

PennWest




Scheme Performance – Well 100/07-36

PennWest




Scheme Performance – Well 100/07-36


PennWest



100/02-06-083-17W5




100/15-36-082-18W5



Scheme Performance – Well 102/15-06


PennWest



Scheme Performance – Well 102/15-06

Bottomhole Conditions


PennWest



Scheme Performance – Well 102/15-06

Bottomhole Conditions


PennWest



Scheme Performance – Well 102/15-06

Bottomhole Conditions

PennWest




Scheme Performance – Well 102/15-06


PennWest



100/10-06-083-17W5




100/15-06-083-17W5



Scheme Performance – Well 103/14-06


PennWest



Scheme Performance – Well 103/14-06


Bottomhole Conditions

PennWest




Scheme Performance – Well 103/14-06


PennWest



100/11-06-083-17W5




102/14-06-083-17W5




Scheme Performance – Steam Injection

PennWest



Scheme Performance – Offsetting Primary Wells

PennWest



- Offsetting primary wells are thermally compatible
- To date, Penn West has not identified any communication between the thermal wells and the offsetting primary wells
- Temperature of the produced fluids is monitored to identify any potential steam migration, and will be shut in if temperatures show a significant increase

Scheme Performance – Recovery Factor

PennWest

| | |
|--|--------------|
| Cycle 1 Production, m ³ | 2,067 |
| Cycle 2 Production to Date, m ³ | 1,335 |
| Total Production to Date, m³ | 3,402 |
| OBIP, m ³ | 5,441,000 |
| Current Recovery, % | 0.1% |
| Estimated Ultimate Recovery*, % | 3% |

*Estimated Ultimate Recovery is low due to the large project area defined. Typical primary recovery in this area is 5%.

1. Background
2. Geology
3. Drilling and Completions
4. Artificial Lift
5. Well Instrumentation
6. 4D Seismic
7. Scheme Performance
- 8. Future Plans**

- Complete second steam cycle on Well 103/14-06 in Q1 2014
- Begin second steam cycle on Well 100/07-36
- Evaluate second production cycles on all three pilot wells to determine third steam cycle schedule
- With the increased injection volumes, Penn West is still early in the evaluation phase of pilot results and the technology's application in the specific reservoir conditions
- Continuously evaluating project economics in light of current market conditions



PennWest


Harmon Valley South HCSS Pilot
Surface Review

1. Facilities
2. Measurement and Reporting
3. Water Use
4. Water Treatment
5. Water and Waste Disposal
6. Sulphur Production
7. Environmental
8. Compliance
9. Non-Compliance
10. Future Plans

- 1. Facilities**
2. Measurement and Reporting
3. Water Use
4. Water Treatment
5. Water and Waste Disposal
6. Sulphur Production
7. Environmental
8. Compliance
9. Non-Compliance
10. Future Plans

Facilities – Pilot Plot Plan

PennWest



PennWest



- Pilot plant facility construction completed in Q4 2013 with the following major equipment:
 - 14.65 MW OTSG
 - Water Treatment Package
 - Water Tank Farm
 - Produced Fluids Tank Farm
 - MCC / Instrument Air Building
 - Diesel and Natural Gas Generators
 - Glycol System
 - HP/LP Flare
 - Three HCSS wells with electrically powered pump jacks

- Drilled one horizontal source water well (14-25-082-18W5) and one vertical source water well (16-36-082-18W5) and connected to the facility via pipeline in Q3 2013
- Constructed 8" 23.4km fuel gas pipeline from TransCanada 05-09-085-17W5 to pilot facility
- Constructed telecommunications infrastructure in Q3 2013 including tower, microwave and radio equipment and UPS

- Bitumen Treatment:
 - Successfully produced sales spec oil with existing facility
 - Each production well is tied into common header/production system
- Steam Generation:
 - OTSG capacity 14.65MW and 80% steam quality
 - Design to steam one well at a time
 - Have not run the OTSG consistently at full capacity and steam quality due to injectivity constraints caused by the reservoir conditions

■ Other Equipment:

- Genset Packages: installed diesel and natural gas generators. Downtime for various reasons, such as overcurrent trips, cooked wires, detonation problems, fan failure, VFD faults.
- Glycol Heaters: Downtime caused by variety of reasons, such as overloads, coolant leaks, cooked VFD, VFD faults.
- The fuel gas lines were mostly installed without insulation or heat tracing – moisture in lines caused variety of problems and equipment trips.

- Radar level transmitters in produced fluids tanks failed to provide correct tank level feedback. Tank level gauges installed instead.
- Significant work required to swing well from steaming to production service. In future, use spectacle blinds instead of removable spools in places where possible.
- The flare knock-out drum was not fitted with separate liquid transfer pump. The vacuum truck is used as a solution. Operating costs should be considered when looking into decisions aimed at capital savings.

- Harmon Valley South Thermal Pilot operates using an natural gas generator with a diesel generator as back-up.

Facility Performance – Fuel Use

PennWest

| | Purchased Gas | Vent Gas | Flare Gas | Produced Gas | Produced Gas Recovery |
|--------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-----------------------|
| Month | e ³ m ³ | e ³ m ³ | e ³ m ³ | e ³ m ³ | % |
| Jul-13 | 22.3 | 0 | 0 | 0 | 0% |
| Aug-13 | 206.4 | 0 | 0 | 0 | 0% |
| Sep-13 | 186.5 | 0 | 0 | 0 | 0% |
| Oct-13 | 239.9 | 0 | 0 | 0 | 0% |
| Nov-13 | 304.7 | 0 | 18.1 | 0 | 0% |
| Dec-13 | 639.5 | 0 | 6.2 | 0 | 0% |
| Jan-14 | 389.6 | 0 | 6.2 | 0 | 0% |
| Feb-14 | 277.3 | 0 | 6.2 | 0 | 0% |
| Mar-14 | 280.6 | 0 | 6.2 | 0 | 0% |
| Apr-14 | 210.9 | 0 | 5 | 0 | 0% |
| May-14 | 261.2 | 0 | 6.9 | 0.1 | 0% |
| Jun-14 | 293.7 | 0 | 11.5 | 0.3 | 0% |
| Jul-14 | 73.5 | 0 | 6.9 | 0.3 | 0% |
| Aug-14 | 92.4 | 0 | 6.7 | 0.2 | 0% |
| Sep-14 | 256.2 | 0 | 3.6 | 0.2 | 0% |
| Oct-14 | 527.2 | 0 | 10.6 | 0 | 0% |
| Nov-14 | 419.7 | 0 | 18.1 | 0 | 0% |
| Dec-14 | 435.7 | 0 | 17.1 | 0.1 | 0% |

1. Facilities
- 2. Measurement and Reporting**
3. Water Use
4. Water Treatment
5. Water and Waste Disposal
6. Sulphur Production
7. Environmental
8. Compliance
9. Non-Compliance
10. Future Plans

- Updated MARP submitted in August 2014 - Revision 6
- Oil production volumes are estimated on lease by tank gauge and measured at the sales point by coriolis meter
- Gas produced with emulsion and casing gas flows directly to HP Flare and is measured by annubar meter. Solution gas from the produced fluid tanks is directed to LP Flare and measured by ultrasonic meter. Both meters to be updated on new MARP revision.
- Steam injection volumes are measured by differential pressure meter across the flow nozzle
- Water to injection facility from source water wells is measured at each well by turbine meters
- Fuel gas supply from TransCanada Pipeline is measured at facility by vortex meters


- Test separator equipped with watercut analyzer used to prorate oil volumes to each well
- Wells put into test on rotation
- Reporting as per Directive 017 requirements

Measurement and Reporting - Proration Factors

PennWest

- Multiple wells producing Jun-14 through Sep-14

Harmon Valley South Proration Factors



Measurement and Reporting – Water Balance **PennWest**

INJECTION FACILITY AB IF 0128299

| Month | TOTAL IN | TOTAL OUT | INVENTORY ADJUSTMENT | BALANCE | |
|--------|----------------|----------------|-------------------------|----------------|-------|
| | m ³ | m ³ | m ³ | m ³ | % |
| Nov-13 | 2,808 | 2,463 | 315 | -29 | 1.0% |
| Dec-13 | 5,420 | 5,428 | -8 | 0 | 0.0% |
| Jan-14 | 2,749 | 2,807 | 26 | 85 | 3.1% |
| Feb-14 | 717 | 908 | -51 | 140 | 19.5% |
| Mar-14 | 3,231 | 3,157 | 71 | -3 | 0.1% |
| Apr-14 | 1,601 | 1,598 | 3 | 0 | 0.0% |
| May-14 | 2,969 | 2,849 | -43 | -164 | 5.5% |
| Jun-14 | 2,515 | 2,544 | -104 | -74 | 3.0% |
| Jul-14 | 0 | 0 | 0 | 0 | 0.0% |
| Aug-14 | 43 | 0 | 41 | -2 | 4.8% |
| Sep-14 | 3,077 | 2,992 | 85 | 0 | 0.0% |
| Oct-14 | 6,081 | 6,117 | -36 | 0 | 0.0% |
| Nov-14 | 4,368 | 4,368 | 0 | 0 | 0.0% |
| Dec-14 | 3,566 | 3,512 | 54 | 0 | 0.0% |

1. Facilities
2. Measurement and Reporting
- 3. Water Use**
4. Water Treatment
5. Water and Waste Disposal
6. Sulphur Production
7. Environmental
8. Compliance
9. Non-Compliance
10. Future Plans

- Water source wells:
1F1/16-36-082-18W5 and
100/14-25-082-18W5
- A Water Act Application
was not required as water
is sourced from the
Paddy-Cadotte Aquifer of
the Peace River
Formation, which is
approximately 4,700 ppm
TDS in this area

| | Brackish Water, m ³ | |
|--------|--------------------------------|--------------------|
| | 1F1/16-36-082-18W5 | 100/14-25-082-18W5 |
| Nov-13 | 461 | 931 |
| Dec-13 | 4,272 | 1,139 |
| Jan-14 | 2,578 | 171 |
| Feb-14 | 592 | 125 |
| Mar-14 | 1,554 | 1,677 |
| Apr-14 | 63 | 1,527 |
| May-14 | 1,347 | 1,622 |
| Jun-14 | 413 | 2,102 |
| Jul-14 | 0 | 0 |
| Aug-14 | 23 | 0 |
| Sep-14 | 1,887 | 1,105 |
| Oct-14 | 6,063 | 18 |
| Nov-14 | 4,313 | 55 |
| Dec-14 | 2,637 | 928 |


1. Facilities
2. Measurement and Reporting
3. Water Use
- 4. Water Treatment**
5. Water and Waste Disposal
6. Sulphur Production
7. Environmental
8. Compliance
9. Non-Compliance
10. Future Plans

- Water Treatment Package designed to treat saline water and produce BFW quality suitable for OTSG
- The source water is treated by a softening system consisting of multimedia filter, primary and secondary WAC softeners, neutralization, regen and dosing systems
- Water Treatment Package designed with condensed equipment and piping spacing, resulting in limited maintenance access
- Separate heated storage for chemicals currently being constructed
- Harmon Valley South Pilot facility does not recycle produced water due to make up water requirements of less than 500 000 m³/year

1. Facilities
2. Measurement and Reporting
3. Water Use
4. Water Treatment
- 5. Water and Waste Disposal**
6. Sulphur Production
7. Environmental
8. Compliance
9. Non-Compliance
10. Future Plans

- Produced water from the facility is sent for disposal to the Class II Disposal facility at 14-18-082-17W5
- Class II Disposal Scheme Approval No. 11913 for disposal in the Leduc Formation

100/14-18-082-17W5 Disposal Well



Includes all disposal water injected at 100/14-18-082-17W5

1. Facilities
2. Measurement and Reporting
3. Water Use
4. Water Treatment
5. Water and Waste Disposal
- 6. Sulphur Production**
7. Environmental
8. Compliance
9. Non-Compliance
10. Future Plans

Sulphur Balance

PennWest

| | Sulphur Production | Sulphur in Flared Gas | Sulphur in Recovered Gas |
|---------------|-------------------------------|----------------------------------|-------------------------------------|
| Month | tonne/d | tonne/d | tonne/d |
| Jan-14 | 0.000 | 0.0000 | 0.0000 |
| Feb-14 | 0.000 | 0.0000 | 0.0000 |
| Mar-14 | 0.000 | 0.0000 | 0.0000 |
| Apr-14 | 0.000 | 0.0000 | 0.0000 |
| May-14 | 0.000 | 0.0000 | 0.0000 |
| Jun-14 | 0.000 | 0.0000 | 0.0000 |
| Jul-14 | 0.000 | 0.0000 | 0.0000 |
| Aug-14 | 0.000 | 0.0000 | 0.0000 |
| Sep-14 | 0.000 | 0.0000 | 0.0000 |
| Oct-14 | 0.000 | 0.0000 | 0.0000 |
| Nov-14 | 0.000 | 0.0000 | 0.0000 |
| Dec-14 | 0.000 | 0.0000 | 0.0000 |

2014 Total Sulphur Production = 0 tonne

- EPEA Approval for Harmon Valley South Pilot facility does not require real-time Sulphur Dioxide (SO₂) emission monitoring
- Site is equipped with passive air monitoring for SO₂, nitrogen dioxide (NO₂) and hydrogen sulphide (H₂S) emissions
- Reports submitted monthly

SO₂ Emissions

PennWest

| | Peak Reading (ppb) | Average Reading (ppb) |
|--------|--------------------|-----------------------|
| Aug-13 | 0.4 | 0.3 |
| Sep-13 | 0.3 | 0.2 |
| Oct-13 | 0.3 | 0.3 |
| Nov-13 | 0.5 | 0.3 |
| Dec-13 | 0.5 | 0.4 |
| Jan-14 | 0.1 | 0.1 |
| Feb-14 | 0.4 | 0.3 |
| Mar-14 | 0.4 | 0.4 |
| Apr-14 | 0.2 | 0.2 |
| May-14 | 2.8 | 1.9 |
| Jun-14 | 0.4 | 0.2 |
| Jul-14 | 0.6 | 0.4 |
| Aug-14 | 0.1 | 0.1 |
| Sep-14 | 0.2 | 0.1 |
| Oct-14 | 0.3 | 0.2 |
| Nov-14 | 0.5 | 0.4 |
| Dec-14 | 0.5 | 0.5 |

1. Facilities
2. Measurement and Reporting
3. Water Use
4. Water Treatment
5. Water and Waste Disposal
6. Sulphur Production
- 7. Environmental**
8. Compliance
9. Non-Compliance
10. Future Plans

- Penn West received EPEA Approval No. 303255-00-00 on October 23, 2012
 - Additional burners on new emulsion tanks added Q2 2014 operating under Director's Authorization
- Monitoring ongoing as per EPEA Approval conditions:
 - Air Emissions
 - Industrial Wastewater and Industrial Runoff
 - Groundwater
 - Soil Monitoring

1. Facilities
2. Measurement and Reporting
3. Water Use
4. Water Treatment
5. Water and Waste Disposal
6. Sulphur Production
7. Environmental
8. **Compliance**
9. Non-Compliance
10. Future Plans

- To the best of our knowledge, Penn West is in compliance with all the requirements and conditions of Commercial Scheme Approval No. 11895C and all other approvals related to the Harmon Valley South HCSS Pilot.

1. Facilities
2. Measurement and Reporting
3. Water Use
4. Water Treatment
5. Water and Waste Disposal
6. Sulphur Production
7. Environmental
8. Compliance
- 9. Non-Compliance**
10. Future Plans

- Jan 2013: High Risk Enforcement due to application for Directive 056 Facility License prior to Directive 042 MARP Approval

- April 2014: Exceeded steam injection volume to 103/14-06-083-17W5 during steam cycle 1
 - Injected 3,569 m³ above 14.5MPa due to faulty cumulative steam calculated tag

1. Facilities
2. Measurement and Reporting
3. Water Use
4. Water Treatment
5. Water and Waste Disposal
6. Sulphur Production
7. Environmental
8. Compliance
9. Non-Compliance
- 10. Future Plans**

- Evaluating project success with increased injection volumes
- Evaluating project economics in light of current market conditions



Questions?



Stock Exchange

Toronto: PWT
New York: PWE

Legal Counsel

Burnet, Duckworth & Palmer LLP

Independent Reserves Evaluator

Sproule Associates Limited

Transfer Agent

Canadian Stock Transfer Company
Toll Free: 1-800-387-0825
Email: inquiries@canstockta.com
Website: www.canstockta.com

Investor Relations

Clayton Paradis Manager, Investor Relations
Telephone: (403) 539-6343
Email: clayton.paradis@pennwest.com

Toll Free: 1-888-770-2633
Email: investor_relations@pennwest.com
Website: www.pennwest.com

Penn West

Suite 200, Penn West Plaza
207 – 9th Avenue SW
Calgary, Alberta, Canada T2P 1K3
Telephone: (403) 777-2707
Toll Free: 1-866-693-2707
Facsimile: (403) 777-2699
Website: www.pennwest.com